

MATERIAL INCLUDED IN ACCOUNT AND REFERENCE NUMBERS FOR PANEL or PACKAGED SWITCH
(R.H. As Shown)

PACKAGED SWITCH	PANEL SWITCH	DESCRIPTION	ACCOUNT AND REFERENCE NO.
OI-842077 R.H. OI-842085 L.H.	OI-814548 R.H. OI-814563 L.H.		
2	2	● 26'-0" Switch Points, Double Reinforcing (I.R.H. curved, I.L.H. straight) C.R. Plan 73178-(-)	See Note No.1
2	2	● 60'-0" Undercut Stock Rail (I.R.H. curved, I.L.H. straight) C.R. Plan 73062-(-)	See Note No.4
4	4	lea. No.1 with Basket, Nos.2,3 & 4 Vertical Switch Rods-Insulated. C.R. Plan 73516-(-)	See Note No.2
3	3	lea. O-G, I-G and 2-G Insulated Gage Plates.	See Note No.3
8	8	No.1 Adjustable Brace Slide Plate	OI-526100
2	2	No.2 " " " "	OI-526126
2	2	No.3 " " " "	OI-526134
12	12	No.1-P Shoulder Slide Plate	OI-526118
2	2	No.4 " " " "	OI-526142
2	2	No.5H Heel Plate (I.R.H. & I.L.H.)	L.H.OI-504628; R.H.OI-504636
2	2	Heel Block Assemblies (I.R.H. & I.L.H.) C.R. Plan 73515-(-)	L.H.OI-101136; R.H.OI-101128
16	16	Adjustable Rail Brace complete with hardware. C.R. Plan 73515-(-)	OI-250354
22 ea.	22 ea.	JR & KR Twin Tie Plates. C.R. Plan 72202-(-)	JR OI-537800; KR OI-538501
—	25	9'-0" Switch Ties	05-061500
—	9	10'-0" " "	05-062508
—	2	13'-0" " " (Headblock) shipped loose	05-065501
4	4	Abrasion Plates	OI-476900
48	48	Cone Neck Drive Spikes 3/4" x 6"	OI-754009
—	96	Rail Anchors	OI-017704
—	378	5/8" x 6" A.R.E.A. Spikes	OI-781428
25	25	Tie Plates C.R. Plan 72022-(-) (4 of which are Altered. Marked on Layout Plan)	OI-534302
18	18	Joint Bars. C.R. Plan 71147-(-)	OI-057609

● These items to be opposite hand for a L.H. Turnout.

ADDITIONAL MATERIAL REQUIRED WITH PANEL or PACKAGED SWITCH TO COMPLETE A TURNOUT

QUANTITY	DESCRIPTION	ACCOUNT and REFERENCE NO.
1	No.15 RBM Frog C.R. Plan 74162-(-)	Less Plates OI-334067 With Plates OI-334083
2	13'-0" Hook Flange Guard Rail. C.R. Plan 71810-(-)	OI-552536
7	FT-20	OI-489218
6	FT-23	OI-489226
2	FT-23 Modified	OI-489390
16	FT-27	OI-489200
2	FT-27 Modified	OI-489408
1	FT-29	— Frog Tie Plates OI-489127
2	FTR-27	C.R. Plan 72105-(-) OI-489457
4	FTR-27 Modified	OI-489424
2	FTR-29	OI-489366
2	FTR-31	OI-489374
2	FTR-33	OI-489382
180	Tie Plates C.R. Plates 72022-(-)	OI-534302
2	Insulated Joints C.R. Plan 71372-(-)	Ins. Only OI-380289; W/Ins. OI-444205
710	5/8" x 6" A.R.E.A. Spikes	OI-781428
54	1/8" x 5/4" Track Bolts, Spring Washers & Nuts Washer OI-875903; B&N OI-231537	

3/4" x 6" Cone Neck Drive Spike are for use in circular holes in plates.

RAILS, INCLUDED IN ACC'T. & REF. NOS. FOR PANEL or PACKAGED SWITCH

QUANTITY	RAIL LENGTHS
8	39'-0" Rail
1	35'-10 9/16" Rail
2	33'-0" Rail
1	22'-5 3/8" Rail
1	19'-6" Rail

All rail ends to be end hardened

TIMBER SHIPPED WITH PANEL SWITCH

TIMBER LENGTHS	9'-0"	10'-0"	11'-0"	12'-0"	13'-0"	14'-0"	15'-0"	16'-0"
ACC'T. & REF. No.	05-061500	05-062508	05-063506	05-064504	05-065501	05-066509	05-067507	05-068505
PANEL SWITCH	25	9	—	—	2	—	—	—

ADDITIONAL TIMBER TO COMPLETE TURNOUT



TIMBER LENGTHS	9'-0"	10'-0"	11'-0"	12'-0"	13'-0"	14'-0"	15'-0"	16'-0"
TURNOUT	0	6	11	9	9	9	8	9

NOTES

- 26'-0" Switch Points—Account and Reference Numbers
R.H. curved OI-650827
L.H. straight OI-650850
R.H. straight OI-650835
L.H. curved OI-650843
- Vertical Switch Rods—Insulated—Account and Reference Nos.
No.1 rod with basket—OI-710787
No.2 rod-----OI-710795
No.3 rod-----OI-710803
No.4 rod-----OI-710811
- Gage Plates—Insulated—Account and Reference Numbers
No.0-G plate---OI-504024
No.1-G plate---OI-504032
No.2-G plate---OI-504040
- 60'-0" Undercut stock rails (straight) for replacement
Account and Reference No. 08-455501 as per C.R. Plan 73062-(-).

CONRAIL 73194-B

STANDARD
NO.15 TURNOUT
RAIL and TIE LAYOUT FOR
BOLTED TRACK - 132 R.E. RAIL
JULY, 1979

 Chief Engineer - Maintenance of Way
 Chief Engineering Officer