


ITEM	APPLICATION	STANDARD ACCOUNT NUMBER	VOLTS	WATTS	TOTAL WATT TOLER.	BULB	BASE	FILAMENT			INITIAL LUMENS	INITIAL LUMENS PER WATT	LUMENS PER WATT TOLER.	MIN. LIFE HRS. AT SERVICE VOLTS	SERVICE VOLTAGE	CHANGE OUT PERIOD	TYPE LIGHTING
								TOLERANCE		SHAPE							
								LCL	LCL-AA								
1	DOUBLET LENS - CLT. (GRS)	49-423492	10.0	18W	±0.9	A-15	3 PS.	2-3/16"	1/64"	CC-6	234	13.0	±1.6	2200	9.5	3 Mos.	Cont. lighted
	DOUBLET LENS - CLT. (GRS)	"	"	"	"	"	"	"	"	"	"	"	"	9.5	1 Year	App. lighted	
2	DOUBLET LENS - CLT. (US&S)	49-423468	10.0	18W	±0.9	A-15	2 PS.	2-7/32"	1/64"	CC-6	234	13.0	±1.6	2200	9.5	3 Mos.	Cont. lighted
	DOUBLET LENS - CLT. (US&S)	"	"	"	"	"	"	"	"	"	"	"	"	9.5	1 Year	App. lighted	
3	DOUBLET LENS - CLT.	49-407453	10.0	18W	±0.9	S-II	SC.	1-1/4"	1/64"	CC-6	234	13.0	±1.6	2200	9.5	3 Mos.	Cont. lighted
	DOUBLET LENS - CLT.	"	"	"	"	"	"	"	"	"	"	"	"	9.5	1 Year	App. lighted	
	SLT., SEV.	"	"	"	"	"	"	"	"	"	"	"	4400	8.3	6 Mos.	Cont. lighted	
	SLT., SEV.	"	"	"	"	"	"	"	"	"	"	"	"	8.3	2 Years	App. lighted	
	SL., MC.	"	"	"	"	"	"	"	"	"	"	"	"	8.3	Burnout		
	PLT. (RED LENS)	"	"	"	"	"	"	"	"	"	"	"	"	8.5	Burnout		
4	UNILENS - CLT. (SAFETRAN) *	49-407628	10.0	25W	±1.0	SPCL	SC.	1-11/16"	.010"	CC-6	393	15.7	±1.5	2200	9.5	3 Mos.	Cont. lighted
	UNILENS - CLT. (SAFETRAN) *	"	"	"	"	"	"	"	"	"	"	"	"	9.5	1 Year	App. lighted	
5	"E" LIGHT, D.E.D. IND.	49-432204	10.0	40W	±0.9	G-16.5	SC.	1-1/4"	1/64"	CC-6			±1.6		9.5	Burnout	
6	PLT. (PL-3)	49-402504	12.0	9W	±0.5	CT-7	SC.	1-1/4"	1/64"	C-2V	96	10.7	±1.3	4400	11.0	Burnout	
7	PLT. (PL-1)	49-402652	12.0	9W	±0.5	G-16.5	2 PS.	1.91"	1/64"	C-2R	96	10.7	±1.3	4400	11.0	Burnout	
8	PLT. (4) DOUBLE FILAMENT	49-386459	12.0	18&5W	±0.9	S-II	SC.	1-1/4"	1/32"	CC-6 & CC-6	285			2200	11.0	BURNOUT OF V*	
9	PLT. (4) SINGLE FILAMENT	49-390204	12.8	18W	±0.9	S-8	SC.	1-1/4"	.04"-.03"	C-6				2200	11.0	Burnout	

TOLERANCE - Plus or minus dimensions in inches allowed on light center length (LCL) and axial alignment (AA). Where two dimensions are shown, the first applies to LCL and the second to AA. Where no tolerance is shown, manufacturer's standard to apply.

* Safetran part * 042293-1

See Notes On Sheets 2 & 3

SHEET 1
CONT'D ON SH 2

CONRAIL  CS-4000-B

STANDARD
ELECTRIC LAMPS

Approved: _____
Chief Engineer C&S Chief Operating Engineer

ISSUE DATE: APR. 15, 1981

Rev. Jan. 26, 1987