


8001-60, FRONT ROD, COMPLETE

APPLIES TO $\frac{119}{136}$ LB. RAIL. FOR 105 LB. RAIL SPECIFY BUSHING, ITEMS 3 OR 4. SEE NOTE 1.



NO	ITEM	REF.	REQ.	REMARKS	ACCT NO
1	Bolt - 3/4-10 X 3-3/4 Std Hd		8		19-443900
2	Nut, 3/4-10NG Hex Electric Stop Nut		8		02-082856
3	Bushing, For 3/4 in. Bolt - Specify if required	GRS P91-265	*	Note 1	02-083448
4	Bushing, " " " " " " " " " " " " " " " "	GRS P91-270	*	Note 1	
5	Lug, R. H.	8001-64	1		
6	Lug, L. H.	8001-65	1		
7	Lug, R. H.	8001-62	1		
8	Lug, L. H.	8001-61	1		
9					
10					
11					
12					
13					
14	Red. Connection	8001-66	1		
15	Red. "	8001-68	1		
16					
17	Sw. Rod Insulation, Complete	AAR 10886	1		
18					
19	Washer Plate, Serrated	8001-67	4		
20					

NOTES:

- For use with 105 Lb. rail, two bushings are required for each lug. Item 4 is required where a point detector lug is attached. Otherwise, item 3 is required.
- Bolts, nuts, and threads to be as specified on plan G35C, MOW switch bolts.
- Material for parts other than nuts and bolts to be C1020 steel.
- Protective treatment to be in accordance with specification CE 234, section 28 or equivalent.
- Account reference numbers are listed on sheet 5.

SHEET 3
CONT'D ON SH 4

CONRAIL **CS-8001**

STANDARD
SWITCH RODS
FRONT RODS FOR SLIP SWITCHES
OPERATED BY GRS SWITCH MACHINES
105, 119, 127, & 140 LB. RAIL
AUG. 6, 1976