


NOTES:

1. This layout to be used for 11'-0", 16'-6", 26'-0", and 39'-0" switch points drilled in accordance with A.R.E.A. standards. For switch dimensions and information not shown on this plan, refer to Maintenance of Way plans for split switches, switch rods, and gage plates.
2. Switch points shown on this plan are 16'-6" long. Due to the bend in the gage plate, it is set back from the edge of the tie to insure that the gage plate bears fully on the tie at the bent stock rail end of the plate. Gage plates for 26'-0" and 39'-0" points, used at this location, are straight and the edge of the gage plate is set at the edge of the tie.
3. Holes in ties for drive spikes, Item 66, to be drilled 1/2" diameter and 5" deep.
4. Locate holes for mounting latch stand base by engaging selector lever and throwbar in each latch stand. Rotate latch stand base as necessary to obtain proper bearing on tie.
5. Bolt, Item 10 is to be installed through operating rod and throw bar coupling with grease fitting on top, nut and cotter key on bottom.
6. This layout may be used with the auxiliary throw layout shown on plan CS-8222 for switches with 39 ft conventional points, or 59 ft. 6 in welded points.
7. Secure end link of switch padlock chain to tie with staple.


SHEET 1  
CONT'D ON SH 2

CONRAIL  CS-8200

STANDARD  
SWITCH LAYOUT

US&S MODEL M-23B SWITCH MACHINE  
119, 132, & 140 LB. RAIL

APR. 10, 1980

Approved:   
Chief Engineer